

PURON® MP Cartridges

Storage Instructions

STORAGE INSTRUCTIONS

A. SHELF LIFE

The PURON MP cartridges leave the factory stored in a glycerin and water solution. From the date of shipment from the manufacturing facility, the cartridge shelf life in the original packaging is one year. This assumes that the sealed bags have not been opened or damaged, and the conditions shown in Sections B&C are met.

B. HANDLING

1. The boxes should not be dropped or crushed.
2. The cartridges should be stored horizontally.

C. CARTRIDGE STORAGE CONDITIONS

1. Keep the cartridges in their original packaging and store in a horizontal position.
2. Store indoors out of direct sunlight.
3. Do not allow the cartridges to dry out or freeze, and they should be kept at less than 40°C (104°F).
4. The preferred long-term storage temperature range is 10°C to 30°C (50 to 85°F), at relative humidity below 70%.

D. USED CARTRIDGE STORAGE SOLUTION

1. **Short and midterm shut-down (up to 30 days):** Cartridges should be thoroughly cleaned once a week and left in water at 5-25°C (41 to 77°F).
2. **Long-term shut-down (30 days or longer):** Cartridges should be cleaned, rinsed and impregnated with 80-100% glycerin before storage.

Once impregnated, the cartridges should be removed from the system and sealed in plastic bags. Storage conditions described in Section C above for new cartridges should also be used for storage of used cartridges.

E. POST-STORAGE CLEANING PROCEDURE

All cartridges should be drained, rinsed and cleaned according to KSS' recommended pre-startup procedures prior to restarting the system on production.

F. WATER QUALITY GUIDELINES

For water quality guidelines for storage solutions please refer to KSS Water Quality Guidelines for cleaning, diafiltration & storage.

The information contained in this publication is believed to be accurate and reliable, but is not to be construed as implying any warranty or guarantee of performance. We assume no responsibility, obligation or liability for results obtained or damages incurred through the application of the information contained herein. Refer to Standard Terms and Conditions of Sale and Performance Warranty documentation for additional information

KOVALUS SEPARATION SOLUTIONS™, LLC • 850 Main Street, Wilmington, MA 01887
Main: +1-978-694-7000 • Toll Free: +1-888-677-5624

For complete contact information and listing of our global locations, visit www.kovalus.com

©2023 KOVALUS SEPARATION SOLUTIONS™, LLC. All rights reserved worldwide. For related patent and trademark information, visit www.kovalus.com/legal.