

ROMICON® 6" Hollow Fiber Cartridges

6" Diameter Hollow Fiber Ultrafiltration Cartridges for Vinegar Filtration

PRODUCT DESCRIPTION

Membrane Polymer:	Polysulfone
Housing Construction:	Polysulfone
Seal/Potting Material:	Proprietary Epoxy Compound
Storage Solution:	Glycerin

PRODUCT SPECIFICATIONS


Part Number	Model	Fiber Diameter mil (mm)	Membrane area ft ² (m ²)
0720277	HF,VINEGAR 6043-97-43-PM500	43 (1.1)	97 (9.0)

OPERATING AND DESIGN INFORMATION*

Maximum Inlet Pressure:	40 psi (2.8 bar)
Maximum Transmembrane Pressure:	35 psi (2.4 bar)
Maximum Operating Temperature (at pH 6.0):	140°F (60°C)
Maximum Cleaning Temperature:	130°F (54°C)
Maximum Permeate Side Back Pressure:	20 psi (1.4 bar)
Maximum Differential Pressure Feed Side:	30 psi (2.1 bar)
Allowable pH:	1.5 – 13.0 @ 130°F (54°C)
Maximum Total Chlorine (During Cleaning):	200 ppm @ pH 10-10.5, 130°F (54°C) 0 ppm @ pH less than 9.5

*Consult KSS Process Technology Group for specific applications.

NOMINAL DIMENSIONS



A		B		C		Permeate Connection	Process Connection
inches	mm	inches	mm	inches	mm		
43	1,092	6.67	169.4	38 ¹¹ / ₁₆	982.7	1 1/2" sanitary	6" sanitary

OPERATING GUIDELINES

Membrane Characteristics:

ROMICON cartridges should be selected for filtration of liquids based on the separation range needed. They provide stable productivity, ease of cleaning and reliable operation. KSS ROMICON cartridges are crossflow-type filters, in which the feed solution is pumped across the cartridge to minimize solids cake buildup on the membrane. Crossflow filters provide efficient filtration at low operating pressure, allowing long process runs while reducing cleaning time, cleaning frequency, and labor costs.

6" HOLLOW FIBER CARTRIDGE HARDWARE

Item	Description		KPN
1	6" Gasket		0090424
2	6" Process Cap Adapter		0040321
3	6" Coupling		1020262
4	2 ½" Cartridge Gasket	EPDM	0090411
		BUNA	0090410
5	2 ½" Coupling		0210468
6	1" Gasket	EPDM	0090394
		BUNA	0090395
7	1" Coupling		0210465
	6" pass kit containing the above parts (EPDM seals)		1007055

Exposure to Chemical Oxidants:

While not recommended for use on a daily basis, exposure to chemical oxidants for thorough cleaning and sanitization may prove necessary and useful.

Potassium metabisulfite (without catalyst such as cobalt) is the preferred chemical to eliminate residual chlorine or similar oxidizers prior to processing process liquid.

Lubricants:

For cartridge installation, use only water or glycerin to lubricate seals. The use of petroleum or vegetable-based oils or solvents may damage the cartridge and will void the warranty.

KSS Capability

KSS is the leader in crossflow membrane technology, manufacturing reverse osmosis, nanofiltration, microfiltration, and ultrafiltration membranes and membrane systems. The industries served include food, dairy and beverage,

pharmaceutical, biotechnology, water and wastewater, semiconductors, automotive, chemical and general manufacturing. KSS adds value by providing top quality membrane products and by sharing its experience in the design and supply of thousands of crossflow membrane systems worldwide.

Service and Ongoing Technical Support

KSS has an experienced staff of professionals available to assist end-users and OEMs for optimization of existing systems and support the development of new applications. Along with the availability of supplemental technical bulletins, KSS also offers a complete line of cleaning chemicals.



The information contained in this publication is believed to be accurate and reliable, but is not to be construed as implying any warranty or guarantee of performance. We assume no responsibility, obligation or liability for results obtained or damages incurred through the application of the information contained herein. Refer to Standard Terms and Conditions of Sale and Performance Warranty documentation for additional information

KOVALUS SEPARATION SOLUTIONS™, LLC. 850 Main Street, Wilmington, MA 01887

Main: +1-978-694-7000 • Toll Free: +1-888-677-5624

For complete contact information and listing of our global locations, visit www.kovalus.com

©2023 KOVALUS SEPARATION SOLUTIONS™, LLC. All rights reserved worldwide. For related patent and trademark information, visit www.kovalus.com/legal.