

**Section 1. Identification**GHS product identifier : **KOCHKLEEN® 630**

Other means of identification : Not available.

Product type : Liquid.

**Relevant identified uses of the substance or mixture and uses advised against**

Product use : Specialty cleaners.

Area of application : Industrial applications.

Supplier/Manufacturer : John R. Hess & Company, Inc.  
400 Station Street  
Cranston, RI  
02910E-mail address of person responsible for this SDS : [custserv@jrhess.com](mailto:custserv@jrhess.com)Emergency telephone number (with hours of operation) : Emergency Number Chemtrec 1-800-424-9300  
John R Hess & Company phone number (information) 1-800-828-4377**Section 2. Hazards identification**OSHA/HCS status : This material is considered hazardous by the OSHA Hazard Communication Standard **(29 CFR 1910.1200)**.Classification of the substance or mixture : FLAMMABLE LIQUIDS - Category 4  
ACUTE TOXICITY (oral) - Category 4  
SKIN CORROSION - Category 1  
SERIOUS EYE DAMAGE - Category 1  
SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract irritation) - Category 3**GHS label elements**

Hazard pictograms :



Signal word : Danger

Hazard statements : Combustible liquid.  
Harmful if swallowed.  
Causes severe skin burns and eye damage.  
May cause respiratory irritation.**Precautionary statements***Date of issue*/*Date of revision* : 05/25/2017*Version* : 2

1/16

## Section 2. Hazards identification

Prevention	: Wear protective gloves. Wear eye or face protection. Wear protective clothing. Keep away from flames and hot surfaces. - No smoking. Use only outdoors or in a well-ventilated area. Avoid breathing vapor. Do not eat, drink or smoke when using this product. Wash hands thoroughly after handling.
Response	: IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Immediately call a POISON CENTER or physician. IF SWALLOWED: Immediately call a POISON CENTER or physician. Rinse mouth. Do NOT induce vomiting. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower. Wash contaminated clothing before reuse. Immediately call a POISON CENTER or physician. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or physician.
Storage	: Store locked up. Store in a well-ventilated place. Keep cool.
Disposal	: Dispose of contents and container in accordance with all local, regional, national and international regulations.
Supplemental label elements	: Do not taste or swallow. Wash thoroughly after handling.
Hazards not otherwise classified	: Causes severe digestive tract burns.

## Section 3. Composition/information on ingredients

Substance/mixture	: Mixture
Other means of identification	: Not available.

### CAS number/other identifiers

CAS number	: Not applicable.
Product code	: Not available.

Ingredient name	Other names	%	CAS number
2-butoxyethanol	2-butoxyethanol	60-100	111-76-2
formic acid	formic acid	5-10	64-18-6
lactic acid	lactic acid	5-10	50-21-5
acetic acid	acetic acid	5-10	64-19-7

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

**There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health and hence require reporting in this section.**

## Section 4. First aid measures

### Description of necessary first aid measures

Eye contact	: Get medical attention immediately. Call a poison center or physician. Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Chemical burns must be treated promptly by a physician.
-------------	--

## Section 4. First aid measures

- Inhalation** : Get medical attention immediately. Call a poison center or physician. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
- Skin contact** : Get medical attention immediately. Call a poison center or physician. Wash contaminated skin with soap and water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Chemical burns must be treated promptly by a physician. Wash clothing before reuse. Clean shoes thoroughly before reuse.
- Ingestion** : Get medical attention immediately. Call a poison center or physician. Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Chemical burns must be treated promptly by a physician. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

### **Most important symptoms/effects, acute and delayed**

#### Potential acute health effects

- Eye contact** : Causes serious eye damage.
- Inhalation** : May cause respiratory irritation.
- Skin contact** : Causes severe burns.
- Ingestion** : Severely corrosive to the digestive tract. Causes severe burns. Harmful if swallowed.

#### Over-exposure signs/symptoms

- Eye contact** : Adverse symptoms may include the following:  
pain  
watering  
redness
- Inhalation** : Adverse symptoms may include the following:  
respiratory tract irritation  
coughing
- Skin contact** : Adverse symptoms may include the following:  
pain or irritation  
redness  
blistering may occur
- Ingestion** : Adverse symptoms may include the following:  
stomach pains

### **Indication of immediate medical attention and special treatment needed, if necessary**

- Notes to physician** : Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
- Specific treatments** : No specific treatment.

## Section 4. First aid measures

- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

See toxicological information (Section 11)

## Section 5. Fire-fighting measures

### Extinguishing media

- Suitable extinguishing media : Use water spray or fog.
- Unsuitable extinguishing media : Do not use water jet. Foam and dry chemical.
- Specific hazards arising from the chemical : Combustible liquid. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. Runoff to sewer may create fire or explosion hazard.
- Hazardous thermal decomposition products : Decomposition products may include the following materials:  
carbon dioxide  
carbon monoxide  
Acetic acid.
- Special protective actions for fire-fighters : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.
- Special protective equipment for fire-fighters : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

## Section 6. Accidental release measures

### Personal precautions, protective equipment and emergency procedures

- For non-emergency personnel : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Do not breathe vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
- For emergency responders : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
- Environmental precautions : Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

### Methods and materials for containment and cleaning up

## Section 6. Accidental release measures

- Small spill : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
- Large spill : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). The spilled material may be neutralized with sodium carbonate, sodium bicarbonate or sodium hydroxide. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

## Section 7. Handling and storage

### Precautions for safe handling

- Protective measures : Put on appropriate personal protective equipment (see Section 8). Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not ingest. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Keep away from alkalis. Empty containers retain product residue and can be hazardous. Do not reuse container.
- Advice on general occupational hygiene : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.
- Conditions for safe storage, including any incompatibilities : Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Eliminate all ignition sources. Separate from alkalis. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

## Section 8. Exposure controls/personal protection

### Control parameters

#### Occupational exposure limits

## Section 8. Exposure controls/personal protection

Ingredient name	Exposure limits
2-butoxyethanol	<p><b>OSHA PEL 1989 (United States, 3/1989).</b>  <b>Absorbed through skin.</b>            TWA: 25 ppm 8 hours.            TWA: 120 mg/m<sup>3</sup> 8 hours.</p>
	<p><b>NIOSH REL (United States, 10/2013).</b>  <b>Absorbed through skin.</b>            TWA: 5 ppm 10 hours.            TWA: 24 mg/m<sup>3</sup> 10 hours.</p>
formic acid	<p><b>ACGIH TLV (United States, 4/2014).</b>            TWA: 20 ppm 8 hours.</p>
	<p><b>OSHA PEL (United States, 2/2013).</b>  <b>Absorbed through skin.</b>            TWA: 50 ppm 8 hours.            TWA: 240 mg/m<sup>3</sup> 8 hours.</p>
acetic acid	<p><b>ACGIH TLV (United States, 4/2014).</b>            TWA: 5 ppm 8 hours. TWA:            9.4 mg/m<sup>3</sup> 8 hours. STEL: 10            ppm 15 minutes. STEL: 19            mg/m<sup>3</sup> 15 minutes.</p>
	<p><b>OSHA PEL 1989 (United States, 3/1989).</b>            TWA: 5 ppm 8 hours.            TWA: 9 mg/m<sup>3</sup> 8 hours.</p>
	<p><b>NIOSH REL (United States, 10/2013).</b>            TWA: 5 ppm 10 hours.            TWA: 9 mg/m<sup>3</sup> 10 hours.</p>
	<p><b>OSHA PEL (United States, 2/2013).</b>            TWA: 5 ppm 8 hours.            TWA: 9 mg/m<sup>3</sup> 8 hours.</p>
	<p><b>ACGIH TLV (United States, 4/2014).</b>            TWA: 10 ppm 8 hours. TWA:            25 mg/m<sup>3</sup> 8 hours. STEL: 15            ppm 15 minutes. STEL: 37            mg/m<sup>3</sup> 15 minutes.</p>
	<p><b>OSHA PEL 1989 (United States, 3/1989).</b>            TWA: 10 ppm 8 hours.            TWA: 25 mg/m<sup>3</sup> 8 hours.</p>
	<p><b>NIOSH REL (United States, 10/2013).</b>            TWA: 10 ppm 10 hours.            TWA: 25 mg/m<sup>3</sup> 10 hours.            STEL: 15 ppm 15 minutes.            STEL: 37 mg/m<sup>3</sup> 15 minutes.</p>
	<p><b>OSHA PEL (United States, 2/2013).</b>            TWA: 10 ppm 8 hours.            TWA: 25 mg/m<sup>3</sup> 8 hours.</p>

Appropriate engineering controls

: Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

## Section 8. Exposure controls/personal protection

**Environmental exposure controls** : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

### Individual protection measures

- Hygiene measures** : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
- Eye/face protection** : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles and/or face shield. If inhalation hazards exist, a full-face respirator may be required instead.
- Skin protection:**
- Hand protection** : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.
- Body protection** : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
- Other skin protection** : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
- Respiratory protection** : Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

## Section 9. Physical and chemical properties

### Appearance

- Physical state** : Liquid. [Clear.]
- Color** : Colorless.
- Odor** : Sharp.
- Odor threshold** : Not available.
- pH** : 1.83 to 1.95 [Conc. (% w/w): 100%]
- Melting point** : Not available.
- Boiling point** : Not available.
- Flash point** : Closed cup: >60.556°C (>141°F)
- Evaporation rate** : Not available.
- Flammability (solid, gas)** : Not applicable.
- Lower and upper explosive (flammable) limits** : Not available.

## Section 9. Physical and chemical properties

<b>Vapor pressure</b>	: Not available.
<b>Vapor density</b>	: Not available.
<b>Relative density</b>	: 0.963 [at 20°C / 68°F]
<b>Solubility</b>	: Soluble in the following materials: cold water and hot water.
<b>Solubility in water</b>	: Not available.
<b>Partition coefficient: n-octanol/water</b>	: Not available.
<b>Auto-ignition temperature</b>	: Not available.
<b>Decomposition temperature</b>	: Not available.
<b>SADT</b>	: Not available.
<b>Viscosity</b>	: Not available.

## Section 10. Stability and reactivity

<b>Reactivity</b>	: No specific test data related to reactivity available for this product or its ingredients.
<b>Chemical stability</b>	: The product is stable.
<b>Possibility of hazardous reactions</b>	: Under normal conditions of storage and use, hazardous reactions will not occur.  Under normal conditions of storage and use, hazardous polymerization will not occur.
<b>Conditions to avoid</b>	: Avoid all possible sources of ignition (spark or flame). Do not pressurize, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition.
<b>Incompatible materials</b>	: Attacks many metals producing extremely flammable hydrogen gas which can form explosive mixtures with air. Reactive or incompatible with the following materials: alkalis oxidizing materials aluminum
<b>Hazardous decomposition products</b>	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## Section 11. Toxicological information

### Information on toxicological effects

#### Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
2-butoxyethanol	LC50 Inhalation Vapor	Rat	450 ppm	4 hours
	LD50 Oral	Rat	917 mg/kg	-
formic acid	LC50 Inhalation Vapor	Rat	7400 mg/m <sup>3</sup>	4 hours
	LD50 Oral	Rat	730 mg/kg	-
lactic acid	LD50 Oral	Rat	3543 mg/kg	-
acetic acid	LC50 Inhalation Dusts and mists	Rat	11000 mg/m <sup>3</sup>	4 hours
	LD50 Dermal	Rabbit	1060 mg/kg	-
	LD50 Oral	Rat	3310 mg/kg	-



## Section 11. Toxicological information

### Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
2-butoxyethanol	Eyes - Moderate irritant	Rabbit	-	24 hours 100 milligrams	-
	Eyes - Severe irritant	Rabbit	-	100 milligrams	-
	Skin - Mild irritant	Rabbit	-	500 milligrams	-
formic acid	Eyes - Severe irritant	Rabbit	-	122 milligrams	-
	Skin - Mild irritant	Rabbit	-	610 milligrams	-
lactic acid	Eyes - Severe irritant	Rabbit	-	750 Micrograms	-
	Skin - Moderate irritant	Rabbit	-	24 hours 100 milligrams	-
	Skin - Severe irritant	Rabbit	-	24 hours 5 milligrams	-
acetic acid	Skin - Severe irritant	Rabbit	-	88 Percent	-
	Eyes - Mild irritant	Rabbit	-	0.5 minutes 5 milligrams	-
	Skin - Mild irritant	Rabbit	-	24 hours 50 milligrams	-
	Skin - Severe irritant	Rabbit	-	525 milligrams	-
	Skin - Mild irritant	Human	-	24 hours 50 milligrams	-

### Sensitization

Not available.

### Mutagenicity

Not available.

### Carcinogenicity

Not available.

### Classification

Product/ingredient name	OSHA	IARC	NTP
2-butoxyethanol	-	3	-

### Reproductive toxicity

Not available.

### Teratogenicity

Not available.

### Specific target organ toxicity (single exposure)

## Section 11. Toxicological information

Name	Category	Route of exposure	Target organs
2-butoxyethanol	Category 3	Not applicable.	Respiratory tract irritation
lactic acid	Category 3	Not applicable.	Respiratory tract irritation

### Specific target organ toxicity (repeated exposure)

Not available.

### Aspiration hazard

Not available.

**Information on the likely routes of exposure** : Routes of entry anticipated: Oral, Dermal, Inhalation.

### Potential acute health effects

- Eye contact : Causes serious eye damage.
- Inhalation : May cause respiratory irritation.
- Skin contact : Causes severe burns.
- Ingestion : Severely corrosive to the digestive tract. Causes severe burns. Harmful if swallowed.

### Symptoms related to the physical, chemical and toxicological characteristics

- Eye contact : Adverse symptoms may include the following:  
pain  
watering  
redness
- Inhalation : Adverse symptoms may include the following:  
respiratory tract irritation  
coughing
- Skin contact : Adverse symptoms may include the following:  
pain or irritation  
redness  
blistering may occur
- Ingestion : Adverse symptoms may include the following:  
stomach pains

### Delayed and immediate effects and also chronic effects from short and long term exposure

#### Short term exposure

Potential immediate effects : Not available.

Potential delayed effects : Not available.

#### Long term exposure

Potential immediate effects : Not available.

Potential delayed effects : Not available.

### Potential chronic health effects

Not available.

## Section 11. Toxicological information

<b>General</b>	: No known significant effects or critical hazards.
<b>Carcinogenicity</b>	: No known significant effects or critical hazards.
<b>Mutagenicity</b>	: No known significant effects or critical hazards.
<b>Teratogenicity</b>	: No known significant effects or critical hazards.
<b>Developmental effects</b>	: No known significant effects or critical hazards.
<b>Fertility effects</b>	: No known significant effects or critical hazards.

### Numerical measures of toxicity

#### Acute toxicity estimates

Route	ATE value
Oral	1019.6 mg/kg
Dermal	12720 mg/kg
Inhalation (vapors)	88.8 mg/l

## Section 12. Ecological information

### Toxicity

Product/ingredient name	Result	Species	Exposure
2-butoxyethanol	Acute EC50 >1000 mg/l Fresh water	Daphnia - Daphnia magna	48 hours
	Acute LC50 800000 µg/l Marine water	Crustaceans - Crangon crangon	48 hours
	Acute LC50 1250000 µg/l Marine water	Fish - Menidia beryllina	96 hours
formic acid	Acute EC50 151200 µg/l Fresh water	Daphnia - Daphnia magna - Larvae	48 hours
	Acute LC50 80000 to 90000 µg/l Marine water	Crustaceans - Carcinus maenas - Adult	48 hours
lactic acid	Acute LC50 257.73 mg/l Fresh water	Fish - Oreochromis mossambicus - Adult	96 hours
acetic acid	Acute EC50 73400 µg/l Fresh water	Algae - Navicula seminulum	96 hours
	Acute EC50 65000 µg/l Fresh water	Daphnia - Daphnia magna - Neonate	48 hours
	Acute LC50 50.1 µl/L Marine water	Crustaceans - Artemia sp.	48 hours
	Acute LC50 75000 µg/l Fresh water	Fish - Lepomis macrochirus	96 hours

### Persistence and degradability

Product/ingredient name	Test	Result	Dose	Inoculum
2-butoxyethanol	301E Ready Biodegradability - Modified OECD Screening Test	95 % - 28 days	-	-
Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability	
2-butoxyethanol	-	-	Readily	
acetic acid	-	-	Readily	

### Bioaccumulative potential

## Section 12. Ecological information

Product/ingredient name	LogP <sub>ow</sub>	BCF	Potential
2-butoxyethanol	0.81	<100	low
formic acid	-2.3	-	low
lactic acid	-0.72	-	low
acetic acid	-0.17	3.16	low

### Mobility in soil

**Soil/water partition coefficient (K<sub>oc</sub>)** : Not available.

**Other adverse effects** : No known significant effects or critical hazards.




## Section 13. Disposal considerations

**Disposal methods** : The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapor from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

United States - RCRA Toxic hazardous waste "U" List

Ingredient	CAS #	Status	Reference number
Formic acid (C,T)	64-18-6	Listed	U123

## Section 14. Transport information

DOT Classification		IMDG	IATA
<b>UN number</b>	UN3265	UN3265	UN3265
<b>UN proper shipping name</b>	Corrosive liquid, acidic, organic, n.o.s. (acetic acid, formic acid) RQ (acetic acid, formic acid)	CORROSIVE LIQUID, ACIDIC, ORGANIC, N.O.S. (acetic acid, formic acid)	Corrosive liquid, acidic, organic, n.o.s. (acetic acid, formic acid)
<b>Transport hazard class(es)</b>	8 	8 	8 
<b>Packing group</b>	II	II	II

Date of issue/Date of revision : 05/25/2017

Version : 2

12/16

## Section 14. Transport information

Environmental hazards	No.	No.	No.
<b>Additional information</b>	<u>Reportable quantity</u> 50000 lbs / 22700 kg [6227.1 gal / 23572.2 L] Package sizes shipped in quantities less than the product reportable quantity are not subject to the RQ (reportable quantity) transportation requirements.  <u>Limited quantity</u> Yes.  <u>Packaging instruction</u> <b>Passenger aircraft</b> Quantity limitation: 1 L  Cargo aircraft Quantity limitation: 30 L  <u>Special provisions</u> B2, IB2, T11, TP2, TP27	<u>Emergency schedules (EmS)</u> F-A, S-B  <u>Special provisions</u> 274	<u>Passenger and Cargo Aircraft</u> Quantity limitation: 1 L Packaging instructions: 851 <u>Cargo Aircraft Only</u> Quantity limitation: 30 L Packaging instructions: 855 <u>Limited Quantities - Passenger Aircraft</u> Quantity limitation: 0.5 L Packaging instructions: Y840  <u>Special provisions</u> A3, A803

**Special precautions for user** : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

**Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code** : Not available.

## Section 15. Regulatory information

**U.S. Federal regulations** : **United States inventory (TSCA 8b):** All components are listed or exempted.  
**Clean Water Act (CWA) 311:** acetic acid; formic acid

**Clean Air Act Section 112 (b) Hazardous Air Pollutants (HAPs)** : Not listed

**Clean Air Act Section 602 Class I Substances** : Not listed

**Clean Air Act Section 602 Class II Substances** : Not listed

**DEA List I Chemicals (Precursor Chemicals)** : Not listed

**DEA List II Chemicals (Essential Chemicals)** : Not listed

**SARA302/304**

**Composition/information on ingredients**

No products were found.

SARA 304 RQ : Not applicable.

**SARA311/312**

Classification : Fire hazard  
Immediate (acute) health hazard

**Composition/information on ingredients**

Name	%	Fire hazard	Sudden release of pressure	Reactive	Immediate (acute) health hazard	Delayed (chronic) health hazard
2-butoxyethanol	60-100	Yes.	No.	No.	Yes.	No.
formic acid	5-10	Yes.	No.	No.	Yes.	No.
lactic acid	5-10	No.	No.	No.	Yes.	No.
acetic acid	5-10	Yes.	No.	No.	Yes.	No.

**SARA313**

	Product name	CAS number	%
<b>Form R - Reporting requirements</b>	2-butoxyethanol	111-76-2	60-100
	formic acid	64-18-6	5-10
<b>Supplier notification</b>	2-butoxyethanol	111-76-2	60-100
	formic acid	64-18-6	5-10

SARA 313 notifications must not be detached from the SDS and any copying and redistribution of the SDS shall include copying and redistribution of the notice attached to copies of the SDS subsequently redistributed.

**State regulations**

- Massachusetts : The following components are listed: 2-BUTOXYETHANOL; ACETIC ACID; FORMIC ACID
- New York : The following components are listed: Acetic acid; Formic acid; Methanoic acid
- New Jersey : The following components are listed: 2-BUTOXY ETHANOL; BUTYL CELLOSOLVE; ACETIC ACID; ETHANOIC ACID; FORMIC ACID
- Pennsylvania : The following components are listed: ETHANOL, 2-BUTOXY-; ACETIC ACID; FORMIC ACID

**California Prop. 65**

None of the components are listed.

**WHMIS Classification:** B3, D2B, E

All known major components of this product are listed on the Canadian DSL.

**WHMIS RATINGS**

Compressed Gas                      Flammable/Combustible X      Oxidizer                                      Acutely Toxic  
Other Toxic Effects      X      Bio Hazardous                                      Corrosive                                      X      Dangerously Reactive

**Hazardous Material Information System (U.S.A.)**

<b>Health</b>	* 3
<b>Flammability</b>	2
<b>Physical hazards</b>	0

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings are not required on SDSs under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered mark of the National Paint & Coatings Association (NPCA). HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.

The customer is responsible for determining the PPE code for this material.

#### National Fire Protection Association (U.S.A.)



Reprinted with permission from NFPA 704-2001, Identification of the Hazards of Materials for Emergency Response Copyright ©1997, National Fire Protection Association, Quincy, MA 02269. This reprinted material is not the complete and official position of the National Fire Protection Association, on the referenced subject which is represented only by the standard in its entirety.

Copyright ©2001, National Fire Protection Association, Quincy, MA 02269. This warning system is intended to be interpreted and applied only by properly trained individuals to identify fire, health and reactivity hazards of chemicals. The user is referred to certain limited number of chemicals with recommended classifications in NFPA 49 and NFPA 325, which would be used as a guideline only. Whether the chemicals are classified by NFPA or not, anyone using the 704 systems to classify chemicals does so at their own risk.

## Section 16. Other information

### History

Date of issue/Date of revision	: 05/25/2017
Date of previous issue	: 05/14/2015
Version	: 2
Prepared by	: HSE Department
Key to abbreviations	: ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor GHS = Globally Harmonized System of Classification and Labelling of Chemicals IATA = International Air Transport Association IBC = Intermediate Bulk Container IMDG = International Maritime Dangerous Goods LogPow = logarithm of the octanol/water partition coefficient MARPOL 73/78 = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution) UN = United Nations

<b>References</b>	: HCS (U.S.A.)- Hazard Communication Standard International transport regulations
-------------------	--



### **DISCLAIMER**

Although the information and recommendations set forth herein (hereinafter "Information") are presented in good faith and believed to be correct as of the date hereof, John R Hess & Company, Inc. makes no representations as to the completeness

## Section 16. Other information

or accuracy thereof. Information is supplied upon the condition that the persons receiving same will make their own determination as to its suitability for their purposes prior to use. In no event will John R Hess & Company, Inc. be responsible for damages of any nature whatsoever resulting from the use of or reliance upon Information. NO REPRESENTATIONS OR WARRANTIES, EITHER EXPRESS OR IMPLIED, OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR OF ANY OTHER NATURE ARE MADE HEREUNDER WITH RESPECT TO INFORMATION OR THE PRODUCT TO WHICH INFORMATION REFERS.

KOCHKLEEN is a registered trademark of Koch Membrane Systems, Inc. in the United States and may be registered in other jurisdictions.

*Date of issue*/*Date of revision* : 05/25/2017

*Version* : 2 16/16